

Case Studies in Innovation: Landmark Mass Timber Projects

Credits: 1.0 AIA/CES HSW LUs, 1.0 PHD credit, 0.10 ICC credit

**Aaron W.
Malone**
LeMessurier



Peter Reiss
ARC



Andreia Teixeira
SHoP Architects



MASS TIMBER+
OFFSITE CONSTRUCTION CONFERENCE

PRODUCED BY



Forest Economic Advisors

WoodWorks | The Wood Products Council is a registered provider of AIA-approved continuing education under Provider Number G516. All registered **AIA CES** Providers must comply with the AIA Standards for Continuing Education Programs. Any questions or concerns about this provider or this learning program may be sent to AIA CES (cessupport@aia.org or (800) AIA 3837, Option 3).

This learning program is registered with **AIA CES** for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

AIA continuing education credit has been reviewed and approved by **AIA CES**. Learners must complete the entire learning program to receive continuing education credit. AIA continuing education Learning Units earned upon completion of this course will be reported to **AIA CES** for AIA members. Certificates of Completion for both AIA members and non-AIA members are available upon request.




Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.

Course Description

Mass timber is redefining what's possible for sustainable, high-performance buildings—from cultural facilities to record-setting commercial towers. This session presents case studies that explore the structural, fire safety, acoustic, and environmental strategies enabling mass timber to meet stringent code requirements while prioritizing occupant wellness and environmental impact. Attendees will learn how design and construction teams overcame technical challenges through integrated processes, innovative detailing, and material optimization, yielding lessons applicable to projects of all scales and types.

Learning Objectives

1. Identify the key code compliance, structural, and fire safety factors that influence the design of large-scale mass timber projects.
2. Describe integrated design strategies that support occupant health, safety, and environmental performance in mass timber buildings.
3. Discuss innovative detailing, material strategies, and construction approaches that enable mass timber to achieve project goals.
4. Apply lessons learned from diverse case studies to inform the design and delivery of future mass timber projects.



American Repertory Theater at Harvard University
David E. and Stacey L. Goel Center for Creativity & Performance

Case Studies in Innovation: Landmark Mass Timber Projects
Mass Timber + October 30, 2025



American Repertory Theater at Harvard University
David E. and Stacey L. Goel Center for Creativity & Performance
Mass Timber + October 30, 2025



Peter Reiss, AIA, LEED AP

Principal with ARC

Architect



Aaron W. Malone, PE

Principal with LeMessurier

Structural Engineer

αΓC.

LeMessurier.




AMERICAN
REPERTORY
THEATER
ART.

Coming



Harvard in Allston: Metropolitan Context




HARVARD

University Planning and Design



Harvard in Allston Property Ownership

Harvard owns a total of
358 acres in Allston.



HARVARD
University Planning and Design

Harvard University - Sustainable Building Standards




A Holistic Building Approach


Targeting Living Building Challenge Core



LBC Core 'petals'



Post occupancy monitoring/ evaluation



A.R.T guiding principles

Peer review process

Sustainability Facts



Low Energy Use Intensity (EUI) Rating = 23

Photovoltaic solar roof panels to generate 50% of the electricity demand


The first Natural Ventilation system in a performance facility on the east coast of America

50% reduction in indoor potable water

Stormwater attenuation systems, including green roofs

Collaboration with Harvard's T.H. Chan School of Public Health

Collaboration with Harvard's Healthier Building Academy to avoid the use of toxic chemicals



Embodied Carbon Reduction

20% reduction in embodied carbon

560 metric tons of carbon saved

equivalent to:

carbon sequestered by 2,060 acres of u.s. forests in one year

co2 emissions from 2,280,873 pounds of coal burned

greenhouse gas emissions from 5,228,936 miles driven by a gasoline powered car

La Cartoucherie
Bois de Vincennes, Paris



La Cartoucherie
Bois de Vincennes, Paris



Bristol Old Vic
Bristol, United Kingdom

Haworth Tompkins



OFFICE
Ticket Collection

BOX OFFICE
Ticket Collection





BOX OFFICE
Ticket Sales



Bristol Old Vic
Bristol, United Kingdom
Haworth Tompkins

New England Regional Context “Saltbox” Houses

Solid Sawn Timber + Masonry




MASS MoCA Building 6
North Adams, MA




John W. Olver Design Building
UMass Amherst
Amherst, MA











2.2.7. Mar 2. 2018

520


Passive assist
natural ventilation



Section east-west



Section north-south



Townhouse

East Stage

Kitchen

Lobby

Yard




← Elevator

West Stage













Type V-A Construction

1-Type IV and Type IV-HT were considered, but would have required:

- a.NFPA 258 testing – and/or addition of FRT plywood outboard from our exterior CLT wall assemblies

Type VA Construction

- a.Height: Limited by Group A (A-1, A-2, A-3) – 3 Stories, 70'.

- b.Area: Limited by Group A – 34,500 SF Max (without frontage). (approx 38,000 with 63% open perimeter)

true 1-hour with char calcs or layers of material/technical data required for all members and all connections





Fire Design

1-hr rating for
Type VA

Combustible but
slow burning


Gypsum at
concealed
Spaces

Char method
for exposed
members


Impact on structural
connections

Mass Timber Structural Design





Construction Sequence




6 in 1

Moisture protection

Shop drawing packages


Phased for sub trade scheduling











THE MECHANICAL PROPERTIES
IMPROVE AS THE DENSITY OF
THE GROWTH RINGS INCREASE.



The mark of
responsible forestry
FSC® C016562
FSC® C002803

BLACK SPRUCE
CROSS SECTION



Mass Timber Procurement

Design Assist
Start of DD

Species
(design values)

Proprietary products

Optimization

Connections
(impact member size)

Schedule

Cost



Timber
Supply

Northern
Quebec

Boreal
Forest

Black spruce
and jack pine

50 frost
free days

Mature at
80-120
years

4" to 6" trunk
diameter



Milled and
conditioned
to
 $1\frac{1}{2}'' \times 2\frac{1}{2}''$
board stock as
short as 18"
length (max
120")

CLT



1-3/8 and 3/4
lam stock
pressed into
orthogonal
layers

Long spans
similar to
concrete on
metal deck

Dimensional
stability and
2-way span

Non-toxic
adhesives

Structure as Architecture

Place a given material where its properties are best suited and where it can serve multiple functions



Exposed structure

Closer coordination


Timber members are larger

Timber spans want to be shorter

12' x 12' Grid (human scale)



Structural Materials



Glulam post + beam
(1300 cubic yards)
(615 tons)

CLT floors and walls
(3600 cubic yards)
(1550 tons)


Structural steel
(592 tons)


Miscellaneous metals
(265 tons)

Concrete (foundations and toppings)
(6160 cubic yards)

Masonry (bearing walls and linings)
(computing)

Structural Materials





Hybrid Approaches

It's ok
to use steel,
sometimes

Compact
members

Steel
flytower

Exterior
conditions



Hybrid Approaches


At the
member
level

Timber-steel
trusses

Steel in timber
connections



Structural Connections





CLT
Walls

Load
Bearing

Resist shear
for wind
and eq

Facade
backup

Fire
separation

Architectural
finish

Floor Assemblies


Concrete toppings

Underlayment

Box in Box


Floating floors

Conduit route




CLT FLOOR/ROOF SLAB ASSEMBLY		CLT FLOOR PANEL SCHEDULE		
		SEE PLAN FOR CLT PANEL MARKS. SEE GENERAL NOTES AND PROJECT SPECIFICATIONS FOR CLT STRESS GRADE AND FURTHER MATERIAL REQUIREMENTS		
CLT PANEL MARK	PANEL LAYUP L = LONGITUDINAL T = TRANSVERSE 35 = 1-3/8" = 34.925mm 19 = 3/4" = 19.05mm	PANEL THICKNESS		
3-PLY 105S	35L - 35T - 35L	4-1/8" (105mm)		
5-PLY 143S	35L - 19T - 35L - 19T - 35L	5-5/8" (143mm)		
5-PLY 175S	35L - 35T - 35L - 35T - 35L	6-7/8" (175mm)		
7-PLY 213L	35L - 35L - 19T - 35L - 19T - 35L - 35L	8-3/8" (213mm)		
7-PLY 244L	35L - 35L - 35T - 35L - 135T - 35L - 35L	9-5/8" (244mm)		


Acoustical Performance




AUDITORIUM AT LOBBY



Acoustical isolation connections



Column-to-column isolation



Column-to-wall isolation





This Concludes The American Institute
of Architects Continuing Education
Systems Course

Build with timber!

Q&A